POWERTRAIN	1.5L GSE T4 Turbocharged e-Hybrid
No. of cylinders, layout	4 – in line
Displacement (cm3)	1469
Bore x stroke (mm)	71.2 x 92.2
Valves per cylinder	4
Compression ratio	12.5:1
ICE Maximum power in kW (hp) @ rpm	95 (130) @ 5500
ICE Max torque in Nm @ rpm	240@1500
E-motor (P2.5) Maximum power in kW (hp)	15 (20)
E-motor (P2.5) Max torque in Nm	55 (135 at gearbox input)
Injection system	Gasoline Direct Injection
Fuel type	Petrol
Hybrid type	48V (BSG + P2.5 E-motor)
TRANSMISSION	
Transmission	7-speed Dual Clutch Automatic
1st	4.462
2nd	2.824
3rd	1.594
4th	1.114
5th	0.851
6th	0.771
7th	0.638
Reverse gear	3.869
Final drive ratio	FD1: 4.176 (1-2-6-7)/ FD2: 4.733 (3-4-5-rev)
Traction	4x2 Front Wheel Drive
PERFORMANCE	
Acceleration: 0-100 km/h (s)	9.7
Max speed (km/h)	191
CONSUMPTION AND EMISSIONS*	
Emission standard	Euro 6d Final
Fuel consumption – combined cycle (I/100km)	5.7 – 6.1
CO2 emissions – combined cycle (g/km)	130 - 139
Fuel tank (litres)	48
WEIGHTS AND DIMENSIONS	,
Kerb weight Std A (kg)	1420
Weight distribution between front/rear (%)	61.6 / 38.4
Height at roof rails (mm)	1684
Width (mm)	1805
Length (mm)	4236

Wheelbase (mm)	2570
Ground clearance (mm)	171 (Std A), 138 (Std C)
Cargo volume (I) with seats up	351
Cargo volume (I) behind first row	1297

<sup>\*</sup>According to WLTP cycle